

FOOT OPERATED GREASE GUN

GURTECH™

Grease Canister

Holds 282 oz / 8 Kg grease
Spend time greasing, not refilling

Patented Pressure Return Valve

Simply lift the foot treadle to return residual pressure back to the canister

- saves grease
- eliminates dribble and mess
- extends grease coupler life
- extends Zerk Nipple life

Ergonomic Carry Handle

Folds away for easy refilling

Foot Operated Treadle

- No more exhausted hands and arms
- Ergonomic operation

Rubber Foot Mounts

Ensures grease gun remains stable while pumping

Patented Lock On Grease Coupler

- Ensures delivery into the joint & bearings, NOT around the Zerk
- Easy lock-on mechanism allows hands-free operation
- Easy clip-off, regardless of line pressure build up. Combined with the Pressure Return Valve, you enjoy a near waste free greasing system



Description	Specifications
Max Delivery Pressure	10,000 psi [690 Bar]
Delivery Rate	0.09 oz [2.7 ml] per stroke
Grease Compatibility	NLGI consistency numbers 0, 1 and 2
Cannister Capacity	282 oz [8 kg]
Delivery Hose	6.5 ft [2 m] x 1/4" [6.35 mm] 2 wire braided hose
Hose Thread	1/8" NPT [male]
Dimensions	L 18 1/2" x W 10 1/4" x H 16 1/2" [L 470 mm x W 260 mm x H 420 mm]
Weight	Dry weight 352 oz [10 Kg]
Pump Activation	Foot operated
Pump Mechanism	2 stage self-priming with pressure return valve
Grease Coupler	Heavy-duty, high pressure. Max working pressure 10,000 psi [690 Bar]. Trigger activated lock-on patented coupler
Patents	US9097385 [others on application]