



## ZENITH LHEP 2

### LOW TEMPERLATURE LUBRICATING GREASE

#### APPLICATIONS

- 저온성에서의 안정성이 매우 뛰어납니다
- 소음억제 및 장기 윤활 시에도 우수한 성능을 발휘합니다
- 사용온도범위: -40℃ ~ 140 ℃
- COLOR : LIGHT BROWN

#### PHYSICAL-CHEMICAL CHARACTERISTICS

시험항목		시험결과	시험방법
증주제, Thickener		Lithium-Soap	
기 유, Base Oil		Synthetic Oil	
혼화주도, 1/10mm		275	KS M ISO 2137
적 점, °C		205	KS M ISO 2176
이유도, wt% (100°C x 24hr)		2.4	KS M 2050
증발량, % (99°C x 22hr)		0.2	KS M 2037
동판부식, 100°C x 24hr		1b	KS M 2088
산화안정도, Kg/cm <sup>2</sup> (99°C x 100hr)		0.2	KS M 2049
저온토오크, gf.cm -40°C	기동	1,900	ASTM D 1478
	회전	800	

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product Material Safety For detailed safety information.

The data given herein are average values and can be modified in further product developments. The end user must check the suitability of the product for each particular application. Unless our technical department is aware and agree on the specific service conditions and application we cannot provide manufacturer liability or property guarantee.