



ZENITH XTR PLUS

CALCIUM COMPLEX GREASE

(수세내수성 및 점착성이 매우 우수하여 부식을 방지하고, 산화안정성과 기계적안정성이 뛰어납니다.)

It has excellent water resistance and adhesion, preventing corrosion, and has excellent oxidation stability and mechanical stability.

APPLICATIONS

- 산업용 장비, 설비의 고하중용 베어링 윤활
- 수분이 접할 수 있는 중장비의 여러 개소
- 수처리 시설의 펌프, 액추레이터 등
- 사용온도범위 : -20 °C ~ 160 °C
- Bearing lubrication for high loads in industrial equipment and facilities
- Several areas of heavy equipment where moisture may come into contact.
- Pumps, actuators, etc. in water treatment facilities
- Operating temperature range: -20 °C ~ 160 °C

증주제 Thickener	Calcium-complex	-
기 유 Base Oil	Mineral oil	-
주 도 Penetration(mm)	280	ASTM D 217
적 점 Dropping Point°C	230	ASTM D 2265
이유도 Oil Separation (%)	2.5	ASDM D 6184
산화안정도 Bomb Oxidation Kg/cm ² DROP (98.9°C X 100hrs)	0.2	ASTM D 942

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product Material Safety for detailed safety information.

The data given herein are average values and can be modified in further product developments. The end user must check the suitability of the product for each particular application. Unless our technical department is aware and agree on the specific service conditions and application we cannot provide manufacturer liability or property guarantee.