



ZENITH RHD-2

WHEEL BEARING GREASE

ZENITH RHD 2는 리튬복합 비누기에 엄선된 고점도 기유와 특수첨가제를 함유하여 광범위한 온도범위와 고속회전에서도 흘러내리지 않으며 우수한 윤활성능을 발휘하는 자동차 휠 베어링 그리스 입니다.

APPLICATIONS

- 고온, 고하중, 고속회전 및 가혹한 운전조건의 각종 산업용 기계에 최적의 그리스 입니다.
- 높은 적점과 뛰어난 점착력으로 고온, 고속회전에서도 흘러내리지 않으며 특히 자동차 휠 베어링에 탁월한 성능을 발휘합니다.
- 산화안정성, 기계적 안정성, 수세내수도 및 점착성이 뛰어납니다.
- 사용온도 범위: -20 ~ 160 °C

PHYSICAL-CHEMICAL CHARACTERISTICS

색 상 (Color)	적색(Red)
NLGI 등급	2
기 유 (Base Oil)	Mineral Oil
증주제 (Thickener)	Lithium Complex
주도 Penetration(mm)	275
적 점 Dropping Point°C	240
4Ball (Shell식- kg)	250
이유도 Oil Separation (%)	1.6
산화안정도 Bomb Oxidation Kg/cm ² DROP (98.9°C X 100hrs)	0.25
동판부식 100°C 24Hr	1a (변화 없음)

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product Material Safety For detailed safety information.

The data given herein are average values and can be modified in further product developments. The end user must check the suitability of the product for each particular application. Unless our technical department is aware and agree on the specific service conditions and application we cannot provide manufacturer liability or property guarantee.